


# ME2S-033-262U3M-SWIR F02

MERCURY2 Super Series 0.3MP CMOS USB3.0 SWIR Camera



GEN<i>i>CAM



The ME2S-033-262U3M-SWIR F02 camera is a SWIR USB3.0 Vision camera with the Sony IMX991 global shutter CMOS sensor and higher performance FPGA. The camera has opto-isolated I/Os that adapt to specific needs. Four-side mounting holes provide maximum installation flexibility for ME2S-U3. Thanks to the extremely compact (29mm × 29mm), robust metal housings and locking screw connectors, the MERCURY2 Super cameras can secure the reliability of cameras deployed in harsh environments.

## Applications

Suitable for applications such as wafer inspection, AOI inspection, spots inspection, medical inspection and so on.


## Features

- Two exposure time modes: Standard / UltraShort
- Two trigger modes: Frame Start / Frame Burst Start
- The Sequencer Control supports multiple sets of parameters configuration
- Support Gamma, Binning, Decimation, Digital Shift and Black Level
- Support Static Defect Correction, Dead Pixel Correct, Sharpness, Noise Reduction, Timer and Counter
- Programmable LUTs and User Set Control
- Support Remove Parameter Limit to expand the range of exposure, gain, and so on
- User Data Area for saving algorithm coefficients and parameter configuration

## Specifications


Model	ME2S-033-262U3M-SWIR F02
Resolution	640(H) × 512(V)
Sensor	Sony IMX991 Global shutter CMOS
Sensor Format	1/4"
Pixel Size	5μm × 5μm
Frame Rate	262.5 fps
ADC	8 bit, 10 bit, 12 bit
Pixel Bit Depth	8 bit, 10 bit, 12 bit
Mono/Color	Mono, SWIR
Pixel Formats	Mono8 / Mono10 / Mono12
SNR	50.9 dB
Exposure Time	UltraShort: 3μs ~ 100μs, Actual Steps: 1 μs; Standard: 13μs ~ 1s, Actual Steps: 1 row period
Gain	0dB ~ 24dB; Default: 0dB, Steps: 0.1dB
Binning	1×1, 1×2, 2×1, 2×2
Decimation	Sensor: 1×1, 2×2
Synchronization	Hardware trigger, software trigger
Acquisition Mode	Single frame, Continuous, Software trigger, Hardware trigger
Reverse X/Y	Reverse X/Y
I/O Interface	1 input and 1 output with opto-isolated, 1 programmable GPIO
Data Interface	USB3.0
Power Supply	12VDC-10%~24VDC+10% supplied via the camera's Hirose connector or power over USB3.0
Typical Power	2.78 W @ 5 VDC
Operating Temp.	0°C ~ +45°C
Storage Temp.	-20°C ~ +70°C
Operating Humidity	10% ~ 80%
Cooling	Passive Cooling, optional: Heat Dissipation Fins
Lens Mount	C
Filters/Transparent Glass	-
Dimensions	29(W) × 29(H) × 38.8(L) mm (without lens adapter, connectors or Heat Dissipation Fins) 85.2(W) × 29(H) × 38.8(L) mm (without lens adapter or connectors, with Heat Dissipation Fins)
Weight	60 g (without Heat Dissipation Fins)
Software	3rd-party software such as HALCON, MERLIC and LabVIEW
OS	32bit / 64bit Windows, Linux, Android, ARMv7, ARMv8
Conformity	CE, RoHS, FCC, ICES, UKCA, USB3.0 Vision®, GenICam®

I/O Interface




Pin	Definition	Description
1	POWER_IN	Camera external power, +12V DC(-10%)~+24V DC(+10%)
2	Line0+	Opto-isolated input +
3	Line2	GPIO input/output
4	Line1+	Opto-isolated output +
5	Line0-/Line1-	Line0-: Opto-isolated input - Line1-: Opto-isolated output -
6	GND	PWR GND & GPIO GND


Spectral Response



Technical Drawing



Without Heat Dissipation Fins



With Heat Dissipation Fins

China Daheng Group, Inc. Beijing Image Vision Technology Branch

12F Daheng Science & Technology Tower, No.3 Suzhou Street, Haidian District, Beijing China, 100080

Tel: +86 10 82828878

E-mail: isales@daheng-imaging.com